



WatchNET

Integrated Digital Technologies



CCTV TESTER

Specifications:

Model	CCTV TESTER
	Video Test
Signal Mode	NTSC / PAL automatically suitable
Display	2.5 inch LCD screen, 960 x 240 resolution
Video Input	1 channel BNC
Video Output	1 channel BNC
	PTZ Controlling
Communication	RS232, RS422 simplex and RS485
Protocol	Pelco D, P, Samsung, Panasonic or customized
Baud Rate	2400, 4800, 9600, 19200
	Other Function
Signal Generating	Output 1 channel video signal for testing monitor
UTB Cable Test	Test UTP cable connection state and display in the screen
RS485 Data Test	Test the RS485 data sent from controlling device
Operation	English OSD Menu
	Power
Power Adapter	DC9V ~ 12V
Battery	2 pcs 18490 standard batteries 3.6, capacity 1400mAh
Rechargeable	5 hours recharging time, work for 5 hours
Low Consumption	Sleeping mode, display battery power state
	Other Parameters
Work Temperature	-30°C ~ +70°C
Work Humidity	30% - 90%
Dimension	170mm x 99mm x 48mm

All product specifications on this brochure are subject to change without notice.



National Sales Office:
351 Ferrier Street, Unit 5
Markham, Ontario
L3R 5Z2, Canada
Tel: 416-410-6865
Fax: 1-866-331-3341
Toll Free: 1-866-843-6865

USA
Suite 105, 275 Cooper Ave
Tonawanda, NY
14150 USA
Toll Free: 1-866-843-6865
Local: (716) 877-7277
Fax: 1-866-331-3341

UAE:
P.O.Box # 8425
Dubai, UAE
Tel: + 971 4 3963067
Fax: + 971 4 3963067
Mobile: + 971 50 5869290

INDIA:
C-116, Lower Level
Lajpat Nagar-II
New Delhi-110024
Tel: + 91 9830677002

