



**KBD-803D**

## FEATURES

- 3D Joystick for Simple Manual Operation
- RS485 Bus Line connect to 32 domes at once
- Large LCD Screen
- Compatible with multiple PTZ Protocol
- Control the Iris, Focus and Zoom as well as 128 presets, tour, scan and patterns

## SPECIFICATIONS

1. Support PELCO matrix	
2. Support 4 keyboards linkage, each keyboard can support 32 domes at most	
3. According to ergonomics design, it is used expediently and comfortably	
4. LCD with back-light, can display command menu, protocol, current camera ID, output display ID and joystick status	
5. Built-in multi-protocol, Baud rate can be selectable	
6. Support all the shortcut key of the dome to handle	
Specification	KBD-803D
Power	9V-12V AC/DC, Power consumption: 5W
Environment	0 <sup>o</sup> ~ +50 <sup>o</sup>
Relative humidity	0-95% (no condensation)
Communication interface	RJ45 interface
Type of interface	RS485 (semi-duplex) & RS-232
Communication speed	2400/4800/9600/19200bps
Transmitting distance	1200m (Rs485,0.5mm twisted pair cable)
Dimension	218x180x55.5(mm)
Weight	N/W: 0.8Kg, G/W: 1.3kg

Authorized Dealer: