

Xtreme weather

Day & Night Camera



-50°C
-58°F

+55°C
+131°F

+55°C
+131°F
0°C
+32°F
-50°C
-58°F



WatchNET

Integrated Digital Technologies



VD-NDV-HT1



Digital Day & Night Vandal Resistant Dome Camera



Features:

- ❖ Vandal & Weather Resistant Housing (IP66)
- ❖ 0.3 Lux/F1.2 (Color), 0.002Lux (Sens-up)
- ❖ 3.8-9.5mm/1.5-3.74in Varifocal DC Auto Iris Lens (F1.3)
- ❖ Various Automatic Functions (DIP Switch Built-In)
 - ESC (Electronic Shutter Control): ON/OFF
On: 1/60(NTSC), 1/50(PAL)-1/100,000sec.
OFF: 1/60sec(NTSC), 1/50sec(PAL)
 - FLK (Flickerless) Mode: ON/OFF
 - BLC (Back Light Compensation) Mode: ON/OFF
 - AWB (Auto White Balance) Mode: ATW/AWB
- ❖ DC Iris Level Adjustment Volume Built-In
- ❖ Color Mode Changing Lux/Term: 15-25Lux/5sec.
- ❖ Day & Night, Electronic IRIS
- ❖ Extreme low temperature tolerance
- ❖ 600TV Lines of Horizontal Resolution
- ❖ Privacy Function
- ❖ 3Axis built-in 120mm Dome Housing
- ❖ High Sensitivity
- ❖ DNR (Digital Noise Reduction)
- ❖ Controlled by OSD Menu

Specifications:

ITEM	NTSC	PAL			
Power Source	AC24V / DC12V	AC24V / DC12V			
	215mA(AC24V) / 250mA(DC12V)	215mA(AC24V) / 250mA(DC12V)			
CCD	Total Pixels	811(H) X 508(V)	795(H) X 596(V)		
	Effective Pixels	768(H) X 494(V)	752(H) X 582(V)		
	Size	1/3 inch interline transfer CCD			
	Scanning System	2:1 interlace			
SYNCH	Synchronization	INT/LL Selectable 0 - 359° (Adjustable)	INT	INT/LL Selectable 0 - 359° (Adjustable)	INT
	Frequency	Horizontal: 15.734 KHz Vertical: 59.94Hz	Horizontal: 15.625 KHz Vertical: 50.00Hz		
ELEMENT	Resolution	600 TV Lines			
	Video Output	1.0Vp-p75 (Video 0.714Vp-p Sync 0.286Vp-p)	1.0Vp-p75 (Video 0.7Vp-p Sync 0.3Vp-p)		
	S/N (Y signal)	50dB (AGC Off)			
	Min. Illumination	0.3Lux / F1.2 (Color), 0.002Lux (Sens-up)			
	COLOR	ON / AUTO			
	Gain Control	OFF / LOW / MIDDLE / HIGH			
	White Balance	ATW / AWC / MANUAL (1,800K - 10,500K)			
	Electronic shutter speed	AUTO / MANUAL (1/60 - 1/120,000)	AUTO / MANUAL (1/50 - 1/120,000)		
	Sens - Up	OFF / AUTO			
	O.S.D	Built-in			
RICAL	Motion Detection	ON / OFF (4 Programmable Zone)			
	DNR	OFF / LOW / MIDDLE / HIGH / (Noise Reduction)			
	MIRROR	Built-in (Horizontal Image Inversion)			
	Privacy Function	ON / OFF (4 Programmable Zone)			
	Operating temperature/Humidity	-50°C ~ +55°C / -58°F ~ 131°F / 30 ~ 90% RH			
Weight	1,100g / 2.400lb				

All product specifications on this brochure are subject to change without notice.

CANADA:
351 Ferrier Street, Unit 5
Markham, Ontario
L3R 5Z2, Canada
Tel: 416-410-6865
Fax: 1-866-331-3341
Toll Free: 1-866-843-6865

USA:
700 Ensminger Rd. Suite 104
Tonawanda, NY 14150 USA
Toll Free: 1-866-843-6865
Local: 1-717-517-8687
Fax: 1-866-331-3341

UAE:
P O Box No 8425
Dubai, UAE
Tel: + 971 4 3584458
Fax: + 971 4 3584458
Mobile: + 971 50 5869290

INDIA:
CE-98, Ground Floor
Lajpat Nagar-I
New Delhi-110024
Toll: +91 11 29824005
Fax: +91 11 29824006

Division of
Videon
Integrated Digital Technologies Ltd.

