



E-Series 32CH DVR



CE FC U

E-96032RTSH-KIT

WatchNET

Integrated Digital Technologies



Embedded DVR Main Features:

- ❖ Hi performance DVR with HDMI & eSATA Port
- ❖ Enhanced H.264 compression algorithm save HDD space & low bandwidth
- ❖ 800/960 fps recording for CIF and special 2 channel 4CIF Real time recording
- ❖ Multiple control methods: Front panel, IR remote controller, keyboard, USB mouse and network keyboard
- ❖ Real time live display up to 32 cameras with 720P high definition
- ❖ Variable frame recording on event with Hi Resolution switching
- ❖ Dual encoding streams support, flexible for network transmission and mobile phone monitoring
- ❖ Alarm triggering, OSD, siren, PTZ preset, e-mail, FTP upload
- ❖ Pentaplex function: live, recording, playback, backup & remote access
- ❖ 4, 8 and 16 Channel simultaneous playback
- ❖ Networking access for remote live viewing, recording, playback, setting, system status, event log
- ❖ Smart video motion detection, camera mask, video loss
- ❖ Smart camera settings: privacy masking, camera lock, color setting, and title display, virtual fence, smart motion search
- ❖ PTZ cameras up to 60 protocols supported
- ❖ 3D mouse control for PTZ cameras
- ❖ Powerful 64 channel network software: built-in web server, multi-DVR client, mobile surveillance software for smart phone & CMS

Powerful Time Grid Search Function
like PC Based DVR

HDMI[®]

HIGH-DEFINITION MULTIMEDIA INTERFACE

eSATA PORT



64 Channel NVR Client
with IP & Megapixel camera integration included

www.watchnetdvr.com

Division of
Videon
Integrated Digital Technologies Ltd.




Embedded DVR Technical Specifications

Model	E-96032RTSH-KIT		
System			
Main Processor	High performance embedded micro processor		
Operating System	Embedded LINUX		
System Resources	Pentaplex function: live, recording, playback, backup & remote access		
User Interface	GUI, on-screen menu tips, Grid search		
Control Device	Front panel, USB mouse, keyboard, IR remote control, network keyboard		
Input Method	Alpha numeric / Denotation		
System Status	HDD status, data stream statistics, log record, bios version, on-line user etc.		
Video			
Video Input	32 channel, BNC, 1.0Vp-p, 75Ω		
Video Output	1 channel TV output, BNC, 1.0Vp-p, 75Ω, 1 VGA output, 1 HDMI output, 1 Matrix output		
Video Standards	PAL(625Line, 50f/s), NTSC(525Line, 60f/s)		
Video Compression	Format	NTSC	PAL
	D1(4CIF)	704 X 480	704 X 576
	CIF	352 X 240	352 X 288
	2CIF	704 X 480	704 X 288
Video Recording	QCIF	176 X 120	176 X 144
	CIF/QCIF: PAL 1f/s-25f/s, NTSC 1f/s-30f/s		
	2CIF: PAL 12f/s / NTSN 15f/s		
	4CIF: PAL 6f/s / NTSC 7.5f/s		
Video Display Split	Dual video encoding streams supported		
	D1@30fps only on Ch1 / Ch4 for 16 channel DVR		
Sequential Display	Supported		
Image Quality	1-6 level(level 6 is the best)		
Privacy Masking	4 self-defined four-sided zones for privacy masking for each camera		
Covert Camera	Hide camera from viewing		
Camera Adjustment	2 Color schedule time period day/night		
Video Information	Camera title, time, video loss, camera lock, motion detection, recording		
TV Output Adjustment	Adjust TV output color & display zone		
Audio			
Audio Input	16 channel, BNC, 200-2800mV, 30KΩ		
Bidirectional Talk Input	1 channel, BNC, 200-2800mV, 30KΩ, same with the 1 st channel		
Audio Output	1 channel, BNC, 200-3000mv, 5KΩ		
Audio Compression	Enhanced G.711 Compression		
Video Detection & Alarm			
Motion Detection	Micro Grid and 396 (22*18) detection zones Sensitivity: 1-6 (level 6 is highest) Record, preset, PTZ, alarm, pop-up, email, FTP		
Video Loss/Camera Mask	Trigger recording, PTZ movement, tour, alarm, email		
Alarm Input	4 channel, programmable, ground, manual open/closed Trigger recording, PTZ movement tour, alarm, email	8 channel, programmable, ground, manual open/closed Trigger recording, PTZ movement tour, alarm, email	16 channel, programmable, ground, manual open/closed Trigger recording, PTZ movement tour, alarm, email
Relay output	6 relay output, 30VDC, 1A, NO/NC, form-C		
Video Virtual Fence	Configurable 8 zone detection		
Hard Disk			
HDD Space	8 SATA HDD up to 2TB		
HDD Management	Audio: 14.4MB/H Video: 56 - 500MB/H		
Auxiliary Interface			
USB Interface	2 ports, 1 for mouse control, 1 for backup		
RS232	Keyboard, PC communication		
RS485	PTZ control		


Model	E-96032RTSH-KIT
Network	
Interface	RJ-45 Port (10/100M)
Network Function	TCP/IP, UDP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Email, Alarm Server, RSTP, RTP
Remote Operation	Monitor, PTZ control, playback, system setting, file download, log information
Record, Playback & Backup	
Recording Mode	Manual, continuous, motion detection, camera mask, video loss, area detection, alarm input
Recording Priority	Manual > Alarm > Video Detection > Continuous
Recording Interval	1 to 120 minutes (default: 60 minutes), Pre-record up to 30 seconds, Post-record up to 5 minutes
Overwrite Mode	Supported FIFO
Micro Grid Search	Time/Date, Alarm, Motion Detection, area search, exact search (accurate to second)
Playback	4, 8 and 16 channel playback simultaneously, pause, stop, rewind, fast play, slow play, next file, previous file, next camera, previous camera, full screen, repeat, shuffle, backup selection
Digital Zoom	Selected zone can zoom into full screen during playback
Backup Mode	Flash disk/ USB HDD/ USB CD/DVD-RW/ / Network download
Environmental	
Power Supply	220V 50Hz / 110V 60Hz
Power consumption	25W
Working Temperature	-10° ~ +55°
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa~106kpa
Dimension	2U, 540mm x 540mm x 240mm (W*D*H)
Weight	12KG (without HDD)
Mounting	Desktop / Rack Mount
Integration	
ATM	All major ATMs integrated through Network
POS	Text Display & Alarm Search Supported

All product specifications on this brochure are subject to change without notice.

Model Reference Chart



Connection Diagram





Embedded 8TB DVRs, CMS & PTZ
with Auto Trace Function & POS Integration




Real Time
Stand Alone ATM DVR



Mobile DVR with
Real time GPS Tracking/Viewing



Intelligent Motion Tracking



Megapixel NVR Hybrid
Scalable from 4 to 64 Channels



XDD
XTREME DIGITAL DYNAMICS

Ultra Hi Resolution Vandal Dome Camera

Canada
351 Ferrier Street, Unit 5
Markham, ON L3R 5Z2
Toll Free: 1-866-843-6865
Tel: 416-410-6865
Fax: 1-866-331-3341

USA
700 Ensminger Rd. Suite 104
Tonawanda, NY 14150 USA
Toll Free: 1-866-843-6865
Local: 1-717-517-8687
Fax: 1-866-331-3341

info@watchnetdvr.com
www.watchnetdvr.com

INDIA:
E-98, Ground Floor
Lajpat Nagar-I
New Delhi-110024
Toll: +91 11 29824005
Fax: +91 11 29824005

UAE:
P O Box No 8425
Dubai, UAE
Tel: + 971 4 3963067
Fax: + 971 4 3963067
Mobile : + 971 50 5869290